

PATENT APPLICATION  
of  
ROGER KEITH RUSSELL  
JAMES EDMOND BEYLOTTE  
and  
RALPH P. PALMER  
for  
ELECTRONIC TOKEN AND LOCK CORE  
Client Reference B-262  
Attorney Docket 3054-73432

## ELECTRONIC TOKEN AND LOCK CORE

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. Patent Application Serial No. 10/115,749, filed on April 3, 2002, which is a continuation of U.S. Patent Application Serial No. 09/287,981, filed on April 7, 1999, now U.S. Patent No. 6,442,986, which claimed the benefit of U.S. Provisional Patent Application Serial No. 60/080974 filed on April 7, 1998, the disclosures of which are hereby incorporated by reference herein in their entirety.

## BACKGROUND AND SUMMARY

The present invention relates to electronic tokens and lock cores that cooperate to determine if access should be granted to the user of the token. More particularly, the present invention relates to electronic lock cores that are interchangeable.

Conventional locksets include a lock cylinder, a lock core that fits within the lock cylinder, and a token that cooperates with the lock core. The lock cylinder can take many forms. For example, the lock cylinder may be a padlock or part of a mortise lockset or cylindrical lockset. No matter what form the lock cylinder takes, the lock cylinder includes an opening that receives the lock core. Traditionally, the lock cores have included mechanical features that cooperated with a mechanical token to determine if the user of the token is granted or denied access through the lockset. See, for example, U.S. Patent Nos. 4,424,693, 4,444,034, and 4,386,510.

Electronic access control systems interrogate a token having stored codes therein and compare the token codes with valid access codes before providing access to an area. See, for example, U.S. Pat. No. 5,351,042. If the token being interrogated has a valid access code, the electronic access control system interacts with portions of a lockset to permit the user of the token to gain access to the area protected by the lockset.

Access control systems may include mechanical and electrical access components to require that a token include both a valid "mechanical code", for

example, an appropriately configured bitted blade to properly position mechanical tumblers, and the valid electronic access code before the user of the token is granted access. See, for example, U.S. Pat. Nos. 5,826,450, 5,768,925, and 5,685,182. Many of these electro-mechanical access control systems use power sources and access code validation systems which are not situated in the lock core and token and are thus  
5 connected by separate circuitry to the lock core.

An interchangeable lock core that is configured to communicate with a token having an access code and a bitted blade in accordance with the present invention includes a core body, a lock actuator that is coupled to the core body for  
10 movement relative to the core body, a token communicator coupled to the core body, and a blocker movable between a first position wherein the lock actuator is fixed to the core body and a second position wherein the lock actuator is movable relative to the core body and means for moving the blocker between the first and second positions, the moving means being coupled to the token communicator and positioned  
15 in the core body. The moving means may include an electromagnet, a blocking member that is permitted movement by the electromagnet between the first and second positions, and means for storing energy acquired from the token interacting with the lock core and later using that energy to maintain the blocking member in the second position until the token is removed from the lock core. In alternative  
20 embodiments the storing means may be a spring or a permanent magnet.

An alternative embodiment of lock core includes a core body, a lock actuator coupled to the core body for movement relative to the core body, a token communicator coupled to the core body, and an electrical portion coupled to the core body. The electrical portion including a blocker movable between a first position  
25 wherein the blocker fixes the position of the lock actuator relative to the core body and a second position wherein the blocker permits movement of the lock actuator relative to the core body, the blocker being pivotable relative to the core body about the center of mass of the blocker. A power supply in one of the token and the core body provides power to the token communicator and an electromagnet controlled by  
30 the token communicator, wherein the power supply provides current to the electromagnet under the control of the token communicator so as to provide a short

pulse of current to the electromagnet. The blocker is sustained in the second position by a biasing mechanism separate from the electromagnet.

Alternative embodiments of the lock core include a passageway formed in the lock actuator, a tumbler barrel partially formed in the core body and  
5 partially formed in the lock actuator, the tumbler barrel being in communication with the passageway, and a plurality of tumbler pins contained in the tumbler barrel, the bitted blade engages a tumbler pin when inserted in the passage way and positions the plurality of tumbler pins in the tumbler barrel to allow movement of the lock actuator with respect to the core body.

10 Additional alternative embodiments of lock core include a first spring capable of biasing the blocking member toward the first position and a second spring capable of biasing the blocking member toward the second position, when the blade of the token is received in the passageway the second spring stores internal energy generated by insertion of the blade to bias the blocking member toward the second  
15 position regardless of the access code contained in the token. When the blade is received in the passageway, the electromagnet is energized if the token contains an authorized access code and the latch is decoupled from the blocking body which is urged to the second position by the energy stored in the second spring. The movement of the blocking body to the second position stores internal energy in the  
20 first spring. A third spring biases the latch toward engagement with the blocking member.

A method of a token interacting with a lock core includes the steps of providing a token having a token access code and a lock core, the lock core including a token communicator, a core body, a lock actuator coupled to the core body for  
25 movement relative to the core body, a blocker movable between a first position preventing movement of the lock actuator relative to the core body and a second position permitting movement of the lock actuator relative to the core body, an electromagnet, an arm coupled to the electromagnet for movement by the electromagnet between a first position in contact with the blocker and a second  
30 position spaced apart from the first position, a first biasing member configured to bias the blocker toward its second position, a second biasing member configured to bias the blocker toward its second position, and a token contact coupled to at least one of

the springs, placing the token in a position to contact the token contact of the lock core and provide energy to the first biasing member, placing the token in a position to communicate with the token communicator of the lock core so that the token communicator can determine if the token access code of the token is valid, energizing  
5 the electromagnet if the token is valid to move the arm from its first position to its second position and permit the first biasing member to move the blocker from its first position to its second position, deenergizing the electromagnet to move the arm to its first position, and moving the token away from the token contact of the lock core to permit the second biasing member to move the blocker to its second position.

10 Additional features and advantages of the present invention will become apparent to those skilled in the art upon consideration of the following detailed description of preferred embodiments exemplifying the best mode of carrying out the invention as presently perceived.

## 15 BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective view of a token, a lock core, and a lock cylinder, the lock cylinder being formed to include an aperture to receive the lock core, and the lock core being formed to include a passageway to receive the token;

20 Fig. 2 is a sectional view, taken along line 2-2 of Fig. 1, showing the lock core including a mechanical portion having two tumbler pin barrels on the left side of the lock core and an electrical portion having a circuit, actuator, and mechanical linkage;

25 Fig. 3 is a sectional view similar to Fig. 2 showing the token positioned to lie in the passageway formed in the lock core, the token including a mechanical portion (bitted blade) and an electrical portion (phantom lines), the mechanical portion of the token interacting with the mechanical portion of the lock core, and the token engaging the mechanical linkage of the electrical portion of the lock core;

30 Fig. 4 is a sectional view similar to Figs. 2 and 3 showing the circuit and actuator moving the mechanical linkage to permit the token to operate the lock core;

Fig. 5 is a sectional view taken along line 5-5 of Fig. 2 showing the lock core including a core body, a key plug positioned to lie within the core body and

formed to include the passageway to receive the token, a control sleeve positioned to lie between the core body and key plug, a control lug appended to the control sleeve, and tumbler pins coupling the core body, control sleeve, and key plug together;

Fig. 6 is a sectional view similar to Fig. 5 showing a control token  
5 inserted into the lock core and biasing the tumbler pins so that rotation of the control token rotates the control sleeve and key plug relative to the core body;

Fig. 7 is a sectional view similar to Fig. 6 showing an operating token inserted into lock core and biasing the tumbler pins so that rotation of the operating token rotates the key plug relative to the control sleeve and core body;

10 Fig. 8 is an exploded view of a preferred embodiment of an electronic token and lock core showing the lock core including a core body, a mechanical linkage having an energy storage system comprised of springs, bearings, and a cantilevered arm for insertion into the core body, an electromagnetic actuator having a blocker armature for mounting within the core body, a signal-receiving element to be  
15 located in a cavity formed in the front face of the core body, and a key plug having a blocker-receiving cavity and a keyway for insertion in the core body and showing the token including a bow and a bitted blade for receipt in the keyway, a casing for attachment to the bow, and a power supply and code storage elements lying in the casing;

20 Fig. 9 is a sectional view taken along line 9-9 of Fig. 8 showing the lock core including a mechanical portion having two tumbler pin barrels each containing tumbler pins partially extending into the keyway and blocking rotation of the key plug relative to the core body and an electrical portion including the blocker of the electromagnetic actuator received in the blocker-receiving channel of the key  
25 plug to block rotation of the key plug relative to the core body;

Fig. 10 is a sectional view similar to Fig. 9 with a token of Fig. 8 inserted into the keyway showing the bitted blade of the token aligning the tumbler pins of the mechanical portion of the lock core so that the tumbler pins no longer inhibit rotation of the key plug within the core body and compressing the springs and  
30 rotating the cantilevered arm of the electrical portion of the lock core to store energy within the springs and showing the blocker armature of the electromagnetic actuator still being received in the blocker receiving cavity but being free to rotate out of the

blocker receiving cavity upon receipt of an authorized access signal by the electromagnetic actuator from the circuit after interrogating identification information on the token;

Fig. 11 is a sectional view similar to Fig. 10 showing the blocker armature of the electromagnetic actuator rotated out of the blocker receiving cavity after receipt of an appropriate code from the token allowing the key plug to rotate freely within core body;

Fig. 12 is a sectional view of another preferred embodiment of a lock core showing the lock core including a core body, a key plug having a keyway therethrough, a mechanical portion having two tumbler pin barrels each containing tumbler pins extending into the keyway and positioned to prohibit rotation of the key plug relative to the core body, and an electrical portion having a mechanical energy storage mechanism comprised of a tumbler ball bearing, springs, a blocking body having a step formed therein, a latch engaging the step of the blocking body, and an electromagnetic actuator controlling movement of the latch;

Fig. 13 is a sectional view similar to Fig. 12 with the token of Fig. 8 inserted in the keyway of the key plug so that the bitted blade has positioned the tumbler pins of the mechanical portion in a position which does not inhibit rotation of the key plug relative to the core body and stored energy in the spring of the electrical portion;

Fig. 14 is a sectional view similar to Fig. 13 after the electromagnetic actuator has been energized in response to the receipt of a valid access code from the token and has disengaged the latch from the step formed in the blocking body to allow energy stored in the lower spring to urge the blocking body into a position in which it no longer inhibits rotation of key plug with respect to core body;

Fig. 15 is a sectional view of yet another preferred embodiment of an electronic lock core including a mechanical portion having two tumbler pin barrels each containing tumbler pins partially extending into the keyway and blocking rotation of the key plug relative to the core body and an electrical portion including a flange coupled to a disk that is pivotally attached to an electromagnet extending into a channel to hold the blocker body in a blocker-receiving cavity of the key plug and block rotation of the key plug relative to the core body;

Fig. 16 is an exploded view of the electromagnetic actuator of Fig. 15 showing a core of an electromagnet into which a coil is inserted and a ferrous disk having the flange for receipt in the indentation in the blocker body that is pivotally mounted to the electromagnet;

5                    Fig. 17 is a sectional view taken along line 17-17 of Fig. 15 showing the flange of the ferrous disk received in the indentation in the blocker to prevent movement of the blocker and also showing a mechanical portion similar to that shown in Figs. 9-11;

                    Fig. 18 is a sectional view similar to Fig. 17 with a token as shown in  
10                   Fig. 8 inserted in the keyway showing the electromagnet energized in response to an authorized code to pivot the flange to a position allowing movement of energy storage mechanism;

                    Fig. 19 is a sectional view of yet another preferred embodiment of a lock core according to the present invention, showing the lock core including a  
15                   mechanical portion having two tumbler pin barrels each containing tumbler pins extending partially into the keyway and blocking the rotation of key plug with respect to core body, a mechanical energy storage device having semi-spherical ended tumblers, a coiled spring, a pivotally mounted latch with a blocker end, a storage end, and an indentation, and a torsion spring, and also showing a latch receiving cavity in  
20                   the key plug with the blocker end of the latch received therein, a latch blocker having a tip received in the indentation, and an electromagnetic actuator for moving the latch blocker;

                    Fig. 20 is a sectional view similar to Fig. 19 with a token of Fig. 8 inserted in the keyway so that the bitted blade has positioned the tumbler pins of the  
25                   mechanical portion in a position which does not inhibit rotation of the key plug relative to the core body and has urged the semi-spherical tumblers upward to store energy in the spring that may be released to urge the blocker end of latch from its current position in which it continues to inhibit rotation of the key plug with respect to the core body to a second position (shown in phantom lines) in which blocker end of  
30                   latch is no longer received in the blocker receiving channel;

                    Fig. 21 is a sectional view similar to Fig. 20 showing the blocker end of the latch rotated out of the blocker receiving channel in response to removal of the



tip of the latch blocker from the indentation of the latch after the electromagnet has been momentarily energized in response to receiving an authorized code to free the key plug to rotate with respect to the core body;

Fig. 22 is a sectional view of yet another preferred embodiment of the electronic lock core of the present invention showing a mechanical portion having two tumbler pin barrels each having tumbler pins partially extending into the keyway and blocking rotation of the key plug relative to the core body and a mechanical energy storage device including tumblers, a lower spring, a blocker body having an annular indentation and an upper spring, and a ball bearing received in a sleeve opening at one end adjacent to the blocker body and, at the other end, adjacent to a cam attached to a rotatable shaft, the ball bearing being received in the indentation to block motion of the blocker body;

Fig. 23 is a cross-sectional view similar to Fig. 22 with a token of Fig. 8 received in the keyway aligning the tumbler pins of the mechanical portion to permit rotation of the key plug relative to the core body and compressing the lower spring of the mechanical energy storage device to store energy for moving the blocker body upward upon removal of the ball from the indentation of the blocker body;

Fig. 24 is a cross-sectional view similar to Fig. 23 showing the cam rotated 180 degrees from the position shown in Fig. 23 by a rotatable solenoid in response to a valid access signal thereby allowing the ball to move out of the indentation of the blocker body which has been urged upward by the energy stored in the lower spring so that the blocker body no longer blocks rotation of the key plug relative to the core body;

Fig. 25 is a partially exploded view of another preferred embodiment of a bow cover for a token;

Fig. 26 is a partially exploded view of yet another preferred embodiment of a bow cover;

Fig. 27 is a partially exploded view of yet another preferred embodiment of a bow cover; and

Fig. 28 is a partially exploded view of yet another preferred embodiment of a bow cover.

Figs. 29-44 are flow charts showing the functional operation of several embodiments of the circuit of the electrical portion of the lock core shown in Figs. 2-4;

5 Figs. 45-50 are flow charts showing the functional operation of several embodiments of the electronic portion of the token shown in Figs. 2-4;

Fig. 51 is a sectional view similar to Fig. 2 of another preferred embodiment of a lock core and token positioned to lie in the lock core showing the lock core including an electrical portion, the token including an electrical portion, and the token being an "operating token" which interacts with the electrical portion of the  
10 lock core to permit rotation of a first portion of the lock core;

Fig. 52 is a sectional view similar to Fig. 51 showing the lock core of Fig. 51 and a "control" token positioned to lie in the lock core, the "control" token includes an electrical portion which interacts with the electrical portion of the lock core to permit rotation of a second portion of the lock core;

15 Figs. 53-68 are flow charts showing the functional operation of the circuit of the electrical portion of the lock core shown in Figs. 51 and 52;

Fig. 69 is a sectional view similar to Figs. 2 and 51 of yet another alternative embodiment of a lock core showing the lock core having an electrical portion and a mechanical portion;

20 Fig. 70 is a sectional view similar to Figs. 2, 51, and 69 of yet another alternative embodiment of a lock core showing the lock core having an electrical portion and a mechanical portion;

Fig. 71 is a perspective view of a token according to the present invention showing the token including a bow, a blade having a proximal end coupled to the bow and a distal end spaced apart from the bow, and an electrical portion (phantom lines) having an electrical contact positioned to lie at the distal end of the  
25 blade;

Fig. 72 is a perspective view of a token according to the present invention showing the token including an electrical portion (phantom lines) having an electrical contact positioned to lie on the blade between the proximal and distal ends  
30 of the blade;

Fig. 73 is a perspective view of a token according to the present invention showing the token including an electrical portion (phantom lines) having an inductance coil positioned to lie in the blade;

Fig. 74 is a perspective view of a token having a bow, a bitted blade coupled to the bow, and a cylindrical blade having electrical contacts coupled to the bow, the cylindrical blade extending substantially perpendicular to the bitted blade;

Fig. 75 is a perspective view of a token having a bow and a blade coupled to the bow, the blade having a triangular cross section to define three surfaces and electrical contacts on two of the surfaces;

Fig. 76 is a perspective view of a key showing the key having a bitted blade and an electrical contact on the bitted blade;

Fig. 77 is a perspective view of a token according to the present invention showing the token including a power source (phantom lines) positioned to lie in the blade of the token;

Fig. 78 is a perspective view of another token according to the present invention showing the token including a power source (phantom lines) positioned to lie in the bow of the token;

Fig. 79 is a perspective view of a lock core according to the present invention showing the lock core including a power source (phantom lines);

Fig. 80 is a perspective view of a power charger used to recharge power to tokens;

Fig. 81 is a perspective view of an information programmer used to program tokens charged by the power charger shown in Fig. 59; and

Fig. 82 is a perspective view of a user holding the token, the token including a handle having killswitch and a blade having a mechanical bitted portion and electrical contacts.

#### DETAILED DESCRIPTION OF THE DRAWINGS

An electronic token 10 and lock core 12 in accordance with the present invention are shown in Fig. 1. The electronic token 10 and lock core 12 are components of a lockset that is installed in an entryway to restrict access through the entryway to valid individuals. The electronic token 10 and core 12 may include

mechanical, electrical, and/or electrical/mechanical features that are used to grant or deny access to the user of the token 10. The electronic lock core 12 is interchangeable with a conventional lock core as shown, for example, in U.S. Pat. Nos. 4,444,034, 4,386,510, and 4,424,693. Thus, to change from a conventional  
5 mechanical lock core to the electronic lock core 12, a user must simply remove the mechanical lock core from the lock cylinder 14 and insert the electronic lock core 12 in the same lock cylinder 14.

Additional lockset components shown in Fig. 1 include a conventional lock cylinder 14 having a lock core-receiving aperture 16 and a throw member 18. In  
10 alternative embodiments of the present invention, the cylinder may be replaced by a padlock or any other type of closure or housing that accepts lock cores 12. Throw member 18 is a conventional lockset component and functions to transfer rotation or any type of movement induced by a token from lock core 12 to the rest of a lockset. In alternative embodiments, the throw member 18 may be replaced with any type of  
15 mechanism that performs the function of transferring rotation from the lock core 12 to the rest of the lockset.

The electronic lock core 12 and token 10 operate as a standalone unit and thus lock core 12 does not need to be hard-wired into an electrical system. All power required by lock core 12 and token 10 come from lock core 12 and token 10.  
20 In addition, any other features of the locking system such as access tracking, recombination, clock, display feedback, etc. must be contained within the token 10 and/or lock core 12.

The lock core 12 includes a mechanical portion 20 and an electrical portion 22 that must be satisfied to permit an individual access through the entryway restricted by lock core 12 as shown in Figs. 2-4. The token 10 also includes a  
25 mechanical portion 24 and an electrical portion 26 that cooperate with the mechanical and electrical portions 20, 22 of the lock core 12 to determine if the user of token 10 is permitted to operate the lockset.

Lock core 12 includes a core body 28, a key plug or lock actuator 30  
30 positioned to lie in core body 28, a control sleeve 32 positioned to lie in core body 28, a control lug 34 coupled to control sleeve 32, pin tumbler barrels 36 positioned to lie partially in core body 28 and partially in the key plug 30, and a face plate 39 as

shown, for example, in Figs. 1-7. The pin tumbler barrels 36 comprise the mechanical portion 20 of lock core 12.

Key plug 30 is formed to include a keyway 37 that receives token 10. Keyway 37 is in communication with pin tumbler barrels 36. Key plug 30, control sleeve 32, and control lug 34 are rotatable relative to core body 28 by a token 10 as shown in Figs. 6 and 7. The key plug 30 can be rotated by itself as shown in Fig. 7 and the key plug 30, control sleeve 32, and control lug 34 can be rotated together relative to core body 28 as shown in Fig. 6. When key plug 30 is rotated by itself, token 10 is permitted to rotate throw member 18 and thus cause the lockset to lock or  
10 unlock as desired.

Key plug 30 is one type of lock actuator that transfers movement induced by a token to move a door latch or other component of a lockset. In alternative embodiments of the present invention, key plug 30 may be linearly movable with respect to core body 28 to move a door latch or other component of the  
15 lockset.

When control sleeve 32 and control lug 34 are rotated with key plug 30, control lug 34 is moved in and out of a recess 38 formed in lock cylinder 14 as shown in Figs. 1 and 5-7. When control lug 34 is positioned to lie in recess 38 as shown in Figs. 5 and 7, lock core 12 is securely held within lock cylinder 14. When  
20 control lug 34 is positioned to lie out of recess 38 as shown in Fig. 6, lock core 12 may be slid out of lock cylinder 14.

To rotate key plug 30 alone and, alternatively, control sleeve 32, control lug 34, and key plug 30 together, two different tokens are used with lock core 12. One of the tokens is referred to as an operating token 40 and is used when a user  
25 wants to rotate key plug 30 alone to cause the lockset to lock and unlock. The second token is referred to as a control token 42 and is used when a user wants to rotate key plug 30, control sleeve 32, and control lug 34 to move control lug 34 in and out of recess 38 formed in lock cylinder 14. The operating and control tokens 40, 42 cooperate with tumbler pins 44 positioned to lie in pin tumbler barrels 36 to determine  
30 if key plug 30 is rotated alone or together with control sleeve 32 and control lug 34.

Before a token 40, 42 is inserted into keyway 37 of key plug 30, tumbler pins 44 couple key plug 30 and control sleeve 32 to core body 28 as shown,

for example, in Figs. 2 and 5. When tumbler pins 44 are aligned in this manner, key plug 30 and control sleeve 32 are prevented from rotating relative to core body 28.

The operating token 40 engages tumbler pins 44 to align the faces of tumbler pins 44, as shown in Figs. 2, 3, and 7, so that control sleeve 32 is coupled to core body 28 through tumbler pins 44 and key plug 30 is not coupled to core body 28 or control sleeve 32. This alignment of tumbler pins 44 by operating token 40 permits key plug 30 to rotate alone if all other locking systems of lock core 12 such as electrical portion 22 of lock core 12 are satisfied by operating token 40.

The control token 42 engages tumbler pins 44 to align the faces of tumbler pins 44 as shown in Fig. 6 so that control sleeve 32 is coupled to key plug 30 through tumbler pins 44 and neither key plug 30 nor control sleeve 32 is coupled to core body 28. This alignment of tumbler pins 44 by control token 42 permits key plug 30, control sleeve 32, and control lug 34 to rotate together if all other locking systems of lock core 12 such as electrical portion 22 of lock core 12 are satisfied by control token 42.

The lock core 12 shown in Fig. 1 is a "figure-8 shaped" lock core 12. In alternative embodiments of the present invention, lock cores of other shapes, sizes, and configurations may incorporate the features disclosed in the present invention. For example, many European lock cores have a shape referred to as a Euro-core design. Additional details relating to lock cores 12 that can be used with the present invention are found, for example, in U.S. Pat. Nos. 4,444,034, 4,424,693, and 4,386,510 and are incorporated herein by reference.

The mechanical portion 24 of token 10 includes a bitted blade 46 and the electrical portion 26 includes a circuit 48 and contact or coupling 50. The mechanical portion 20 of lock core 12 includes pin tumbler barrels 36 and tumbler pins 44 that cooperate with bitted blade 46 of token 10. The operation of pin tumbler barrels 36 and tumbler pins 44 are discussed in detail in U.S. Patent Nos. 4,444,034, 4,424,693, and 4,386,510 and are incorporated herein by reference. In alternative embodiments, the mechanical portion 24 of the lock core 12 and token 10 may include any type of mechanism in the lock core that the token must actuate before a user is granted access.

The electrical portion 22 of lock core 12 includes a circuit 52, an actuator 54, a contact and coupling 56, and a mechanical linkage 57. The circuit 52 of lock core 12 and circuit 48 of token 10 communicate through contacts 50, 56. Many types of contacts 50, 56 can be used and placed in many different locations on lock core 12 and token 10. These contacts 50, 56 include ohmic and inductive contacts as discussed in provisional patent application Serial No. 60/080974 filed April 7, 1998 that is expressly incorporated by reference herein.

The circuit 52 of lock core 12 may include various combinations of a token identification reader or token communicator, a lock operator, a recombination system, a token access history, a clock, a power source, a power conditioner, and a power distributor. The circuit 48 of token 10 may include various combinations of token identification information or access code 74, token access history, clock, and power source 82. Various lock core 12 and token 10 configurations having different combinations of the above-mentioned features are illustrated and described in U.S. provisional patent application Serial No. 60/080974 filed April 7, 1998 that is expressly incorporated by reference herein.

Various lock core circuit 52 configurations having different combinations of the above-mentioned features are shown in Figs. 29-44. In all of these circuit configurations, the circuit includes a token identification reader 58 that communicates with a token 10. The token identification reader 58 communicates with a lock operator 60 which determines whether token 10 presented to lock core 12 should be granted or denied access. If lock operator 60 determines that token 10 should be granted access, lock operator 60 communicates with actuator 54 and commands actuator 54 to move mechanical linkage 57 to permit token 10 to rotate key plug 30. If lock operator 60 determines that token 10 should not be granted access, lock operator 60 does not receive an instruction from lock operator 60 to move mechanical linkage 57.

The lock operator 60 is a conventional microprocessor that can be, for example, one of the following components: Microcontroller (PIC12C50X or PIC12C67X from Microchip of Miamisburg, OH; COP8SA series from National Semiconductor; Z8 series from Zilog; 8031 or 8051 series from Intel); Application Specific Integrated Circuit (ASIC); "Custom silicon" circuit.

The actuator 54 cooperates with mechanical linkage 57 to move mechanical linkage 57 between a position preventing rotation of key plug 30 relative to core body 28 and a position permitting rotation of key plug 30 relative to core body 28. The key plug 30 and core body 28 are formed to include chambers 88, 90,  
5 respectively that receive mechanical linkage 57 as shown in Fig. 2-4. Mechanical linkage 57 moves through chambers 88, 90 to couple key plug 30 to core body 28 and uncouple key plug 30 and core body 28. Before either key plug 30 or control lug 34 can be rotated by token 10, actuator 54 must move mechanical linkage 57 to a position to permit key plug 30 to rotate relative to core body 28.

10 Compared to the conventional lock cores, the control sleeve 32 of lock core 12 is shorter to permit mechanical linkage 57 to couple key plug 30 and core body 28 without mechanical linkage 57 having to extend through control sleeve 32. In addition, using a shorter control sleeve 32 provides room for components of lock core circuit 52, actuator 54, and mechanical linkage 57. In alternative embodiments,  
15 the control sleeve can be the same as in conventional lock cores (i.e., not shorter). In this alternative embodiment, the mechanical linkage would extend through the control sleeve to interact with the key plug.

Before a token 10 is inserted into lock core 12, mechanical linkage 57 couples key plug 30 and core body 28 as shown in Fig. 2. When token 10 is inserted  
20 into lock core 12, token 10 engages mechanical linkage 57 as shown in Fig. 3. The engagement between token 10 and mechanical linkage 57 provides energy to mechanical linkage 57 to later assist in moving mechanical linkage 57 if actuator 54 permits mechanical linkage 57 to move. The energy supplied to mechanical linkage 57 by token 10 can be stored by a spring, piezoelectric material/capacitor, elastic  
25 material, or other suitable device. In alternative embodiments, the mechanical linkage does not contact token to receive energy.

After circuit 52 verifies that token 10 should be granted access, actuator 54 moves mechanical linkage 57 to a position shown in Fig.4 to permit key plug 30 to rotate relative to core body 28 if the mechanical portion 20 of lock core 12  
30 is also satisfied by token 10. In the illustrated embodiment, the mechanical linkage 57 includes first and second portions 84, 86 that can be separated. When circuit 52 verifies that token 10 should be granted access, actuator 54 positions mechanical



linkage 57 so that the abutting faces of portions 84, 86 are positioned to lie at the intersection of core body 28 and key plug 30 and key plug 30 can rotate relative to core body 28. In alternative embodiments, when circuit 52 verifies that the token should be granted access, actuator 54 removes the entire mechanical linkage from the  
5 key plug to permit the key plug to rotate relative to the core body.

Because lock core 12 includes pin tumbler barrels 36, token 10 cannot be removed until the token is returned to the same position at which it was inserted as shown in Fig. 3. When token 10 is returned to this position, mechanical linkage 57 moves through chambers 88, 90 without assistance from actuator 54 to couple key  
10 plug 30 and core body 28 to prevent key plug 30 from rotating.

In preferred embodiments, each time lock core circuit 52 causes actuator 54 to activate, actuator 54 activates for a time period of only about 50 milliseconds. Thus, in preferred embodiments, mechanical linkage 57 is a linkage that can be moved to a position to uncouple key plug 30 and core body 28 with  
15 actuator 54 only activated for this short time period. It is preferred to have actuator 54 activated for this short time period to minimize the amount of power consumed by actuator 54. When token 10 is not positioned in lock core 12, it is preferred that mechanical linkage 57 maintain the connection between key plug 30 and core body 28 without actuator 54 consuming power. In alternative embodiments, the actuator can  
20 consume additional power through the cycle of coupling and uncoupling the key plug and core body if suitable power sources that can be housed in lock core and token are available.

Examples of actuator 54 include the following devices: Miniature solenoid (Traditional single-acting solenoid, Double-acting latching solenoid,  
25 Micromachined solenoid similar to the microrelays manufactured by Georgia Institute of Technology, Rotary solenoid of the type sold by Lucas Control Systems of Vandalia, OH); Miniature motor for both rotary and linear actuation (3mm diameter motor, Model SYH30001, made by RMB Miniature Bearings, Inc. of Ringwood, NJ; Miniature motor such as those made by Portescap or Maxon; Micromechanical motor  
30 such as those designed at Massachusetts Institute of Technology and Sandia National Laboratories); Muscle materials (Shape memory alloys such as Flexinol™ wire from Dynalloy, Inc. of Irvine CA; Muscle chemicals such as those emerging from

laboratories at MIT of Cambridge, MA, that change volume in response to electricity, temperature, etc.); Piezo materials (Piezoelectric polymer bimorph, scrolled, or folded actuators such as those made by AMP Sensors).

The first and second portions 84, 86 of mechanical linkage 57 are  
5 provided for illustrative purposes only to describe how actuator 54 moves mechanical linkage 57 to couple and uncouple core body 28 and key plug 30. Mechanical linkage 57 may be any of the following mechanisms: mechanical tumbler pins (The tumbler pins are moved axially into and out of one or more chambers formed in key plug 30, control sleeve 32, and/or core body 28 by actuator 54. The tumbler pins may  
10 include any cross-sectional shape or configuration); one or more fingers, prongs, or pawls moved axially or pivoted into and out of chambers formed in the key plug 30, control sleeve 32, and/or core body 28 by actuator 54 (The fingers or prongs may include any cross-sectional shape or configuration); clutch (A clutch as described in connection with lock core 1312 shown in Fig. 69); friction brake (A friction brake  
15 prevents rotation of key plug 30 and/or control sleeve 32 by placing an axially or radially directed force onto key plug 30 and/or control sleeve 32 that is sufficient to prevent key plug 30 and control sleeve 32 from rotating).

The tumbler pins, fingers, clutch, and friction brake can be moved by actuator 54 using a cam mechanism, screw and nut mechanism, gear mechanisms  
20 including rack and pinion mechanisms, and pneumatic systems.

Any of the above-mentioned linkages can incorporate springs to bias members in certain directions or store energy.

The above-mentioned linkages could be moved through a single axis. However, it is preferred that the linkages be moved through a plurality of axes to  
25 prevent a vandal from rapping (vibrating) the lockset and having the components of the lockset moved to a position where key plug 30 can be rotated. Rapping is the act of vibrating the lockset to cause components of the lockset to move or change state without using an authorized token.

For either operating or control token 40, 42 to operate lock core 12, the  
30 token 40, 42 must satisfy both the mechanical and electrical portions 20, 22 of lock core 12. If the electrical portion 26 of token 40, 42 satisfies the requirements of electrical portion 22 of lock core 12, actuator 54 responds to move mechanical linkage

57 to permit rotation of key plug 28. Simultaneously, the mechanical portion 24 of token 40, 42 must also satisfy mechanical portion 20 of lock core 12 to permit either key plug 30 to rotate alone or key plug 30 to rotate together with control sleeve 32 and control lug 34 depending on the type of token 40, 42 used.

5                   Because electrical portion 22 includes only one actuator 54, mechanical portion 20 of lock core 12 is required to determine if a control token 42 or an operating token 40 has been inserted into keyway 37 of lock core 12. If a proper control or operating token 40, 42 is inserted into lock core 12, lock operator 60 commands actuator 54 to move mechanical linkage 57 to a position permitting key  
10   plug 30 to be rotated relative to core body 28. Thus, mechanical portion 20 of lock core 12 must determine if key plug 30 rotates alone or together with control sleeve 32 and control plug 34. As discussed above, bitted blade 46 of operating token 40 will raise tumbler pins 44 so that only key plug 30 is able to rotate and bitted blade 46 of control token 42 will raise tumbler pins 44 so that key plug 30, control sleeve 32, and  
15   control lug 34 are able to rotate together.

                  In the illustrated embodiment, the mechanical portion 20 of lock core 12 is conventional tumbler pins 44. In alternative embodiments, the mechanical portion of lock core may include any type of mechanical device that distinguishes an operating key from a control key and, in addition, may prevent any of the key plug,  
20   control sleeve, and control lug from rotating unless an appropriate token is presented to the mechanical portion of the lock core. One such alternative embodiment is a spring that is moved when one of the control and operating keys is inserted into the lock core but not when the other of the control and operating keys is inserted.

                  Referring specifically to Figs. 8-11, a first embodiment of lock core  
25   112 and token 110 are illustrated. Electronic lock core 112 includes a core body 128 having an aperture 117, a key plug or lock actuator 130 sized to be received in the aperture 117 and formed to include a keyway 137, a mechanical portion 120, and an electrical portion 122. Mechanical portion 120 includes two pin tumbler barrels 136 each containing tumbler pins 144 partially extending into keyway 137 and blocking  
30   rotation of key plug 130 relative to core body 128, as shown, for example, in Fig. 9, unless a token 110 containing an appropriately bitted blade 146 is inserted in keyway 137, as shown, for example in Figs. 10-11.

Electrical portion 122 of lock core 112 includes a mechanical linkage 157, an electromagnetic actuator 154, a token communicator or coupling 156, and a circuit 152. Coupling 156 and circuit 152 are received in a cavity 159 formed in face plate 139 of core body 128. Electromagnetic actuator 154 includes an armature 161  
5 pivotally supported for movement between first and second angularly displaced positions about a pivot axis 163 extending through center of mass 106 of armature 161, an electromagnet 165 having a pair of opposed pole members 167 extending toward the ends of armature 161 on either side of pivot axis 163, and a three pole permanent magnet 169 extending between pole members 167 of electromagnet 165. Armature  
10 161 is received in a blocker-receiving channel 171 of key plug 130 to block rotation of key plug 130 relative to core body 128 when in the first position. Permanent magnet 169 biases armature 161 in the first position. When armature 161 is in the second position, it is not received in the blocker-receiving channel 171 and key plug 130 is permitted to rotate relative to core body 128.

15 Mechanical linkage 157 includes an energy storage system 173 having a spring 175, a semi-spherical tumbler pin 145 having a first end 104 extending into key way 137 and a spaced apart second end 105 and spherical tumbler pins 177 each including a downwardly facing semi-spherical surface for insertion into a barrel 179 partially formed in core body 128 and partially formed in key plug 130, and a  
20 cantilevered arm 181 for insertion into a cavity 183 in core body 128 in communication with barrel 179. Semi-spherical tumbler pin 145 includes a first end 104 extending into key way 137 and a spaced apart second end 105 engaging one of spherical tumbler pins 177. Each spherical tumbler pin 177 includes a downwardly facing semi-spherical surface.

25 Semi-spherical tumbler pin 145 and spherical tumbler pins 177 are utilized so that tumbler alignment in mechanical linkage 157 does not have to be as precise as the alignment of tumbler pins 144 in mechanical portion 120 in permitting key plug 130 rotation. So long as the downwardly facing semi-spherical surface of one of spherical pins 177 is located at the interface of core body 128 and key plug  
30 130, rotation of key plug 130 will urge that spherical pin 177 upwardly until it is completely positioned within the portion of barrel formed in core body 128. Thus, the location of armature 161 with respect to blocker-receiving channel 171, and not the

location of semi-spherical tumbler pin 145 and spherical tumbler pins 177, determines whether electrical portion 122 inhibits rotation of key plug 130 relative to core body 128. In alternative embodiments, the electrical portion includes tumbler pins similar to tumbler pins 144 instead of pins 145, 177 so that both the location of the armature  
5 161 and the pins determine whether the requirements of the electrical portion are satisfied. Similar barrels 279, 379, 479, and 579, pins 245, 277, 345, 377, 445, 477, 545 and 577 are found in the lock core embodiments 212, 312, 412, and 512 described hereinafter to serve similar functions.

While Fig. 1 illustrates circuitry 48 and contact 50 integrally formed  
10 into the bow of electronic token 10, a presently preferred embodiment of electronic token 110 includes a standard mechanical token 109 having a bitted blade 146 and a bow 108 and a case 107 designed to encase bow 108, as shown, for example, in Fig. 8. Case 107 contains the electrical portion 126 of token 110. Standard token 109 is designed so bitted blade 146 may be received in keyway 137 of key plug 130.  
15 Illustratively electrical portion 126 includes a power supply 182, a coupling 150, incorporated previously by reference, and token identification information 174. Alternative forms of cases 607, 707, 807 and 907 for attachment to standard token bows are shown, for example, in Figs. 25-28, respectively.

Prior to token 110 insertion, tumbler pins 144 partially extend into  
20 keyway 137 and block rotation of the key plug 130 relative to core body 128 as shown in Fig. 9. Rotation of key plug 130 relative to core body 128 is also blocked by armature 161 of electromagnetic actuator 154 which is received in blocker-receiving channel 171 of key plug 130, as shown, for example, in Fig. 9. Armature 161 is inhibited from pivoting out of blocker-receiving channel 171 by cantilevered arm 181,  
25 as well as by permanent magnet 169.

When token 110 is inserted into keyway 137 bitted blade 146 of token  
110 aligns tumbler pins 144 of the mechanical portion 120 so that they no longer inhibit rotation of key plug 130 with respect to core body 128 as shown in Fig. 10. Bitted blade 146 also urges semi-spherical tumbler pin 145 upwardly compressing  
30 spring 175 and causing rotation of arm 181 out of engagement with armature 161 freeing armature 161 to move if electromagnet 165 is energized in response to a valid authorization code. Thus, immediately after insertion of token 110, armature 161 of

electromagnetic actuator 154 is still received in blocker-receiving cavity 171 but is free to rotate out of blocker-receiving cavity 171 upon lock core 112 receiving an authorized access signal from token 110, as shown, for example, in Fig. 10.

Compressed spring 175 stores energy which is used to urge arm 181  
5 back into its initial position upon removal of token 110 from keyway 137, as shown in Fig. 9. This stored energy facilitates the return of armature 161 of electromagnetic actuator 154 to its blocking position in blocker-receiving slot 171.

If token 110 contains token identification information 174 which is authorized to open lock, coil 185 of electromagnet 165 is energized causing armature  
10 161 of electromagnetic actuator 154 to be rotated out of the blocker-receiving cavity 171. Electromagnetic actuator 154 requires only a short energy pulse or trigger pulse to pivot armature 161 to the non-blocking position. Once pivoted to the non-blocking position of Fig. 11, armature 161 remains in that position without continued coil 185 energization. As a result, energy consumption of electronic lock core 112 is  
15 minimized extending the life of batteries used as a power source 182. Operation of a similar electromagnetic actuator 154 is described in depth in Ono et al. U.S. Patent No. 4,703,293, the disclosure of which is incorporated herein by reference.

After the lockset has been configured to grant access to the authorized user, user removes token 110 from keyway 137 allowing the energy stored in  
20 compressed spring 175 to rotate arm 181 which pivots armature 161 of electromagnetic actuator 154 into its blocking position shown in Fig. 10. No electrical energy is required to return armature 161 to its blocking condition further extending the battery life of power source 182.

Referring to Figs. 12-14, a second embodiment of the lock core 212 in  
25 accordance with the present invention is illustrated. Lock core 212 includes core body 228, a key plug or lock actuator 230 having a keyway 237 therethrough, and a mechanical portion 220 including two tumbler pin barrels 236 each containing tumblers pins 244 extending into keyway 237 and blocking rotation of the key plug 230 relative to core body 228. Lock core 212 also includes electrical portion 222  
30 having a coupling or token communicator 256, a circuit 252, an electromagnetic actuator 254, and a mechanical linkage 257. Mechanical linkage 257 includes a mechanical energy storage system 273 having a semi-spherical tumbler pin 245,

spherical tumbler pins 277, a lower spring 275, an upper spring 287, a blocking body 289 having a step 291 formed therein, a latch 281, and blocking body-receiving cavity 271 formed in key plug 230. Electromagnetic actuator 254 is coupled to latch 281 to control the movement of latch 281 between a position lying in step 291 of blocker  
5 body 289 and a position away from step 291.

When token 210 is inserted into keyway 237 of key plug 230, bitted blade 246 positions tumbler pins 244 of mechanical portion 220 so they do not inhibit rotation of the key plug 230 relative to the core body 228 as shown in Fig. 13. Bitted blade 246 also engages semi-spherical tumbler pin 245 and urges it, and spherical  
10 tumbler pins 277, upwardly to compress lower spring 275. After token 210 insertion, but prior to receiving an authorized code, latch 281 is positioned in step 291 preventing blocking body 289 from moving out of blocker body-receiving cavity 271. The energy stored in the lower spring 275 after token insertion is used to urge blocking body 289 upwardly out of blocker body-receiving cavity 271 once latch 281  
15 is urged away from step 291.

After electromagnetic actuator 254 has been energized in response to the receipt of a valid access code, latch 281 is momentarily disengaged from step 291 allowing energy stored in lower spring 275 to urge blocking body 289 into a position in which it no longer inhibits rotation of key plug 230 with respect to core body 228  
20 as shown in Fig. 14. The upward movement of blocking body 289 stores mechanical energy in upper spring 287 which is later used to return blocking body 289 to its blocking position upon removal of token 210 as shown in Fig. 12.

Electromagnetic actuator 254 includes a core 293, a movable element 261, and a spring 292 biasing the movable element 261 away from the core 293. Core  
25 293 has a first end 221 having a cross-sectional area (not shown) and formed to include a circular opening 223 therethrough communicating with a cylindrical axial cavity 225 and a ring-shaped opening 227 therethrough communicating with an annular cavity 229, a closed second end 231, and a cylindrical coil 285 received in the annular cavity 229.

30 Movable element 261 includes a shaft 294 having a first end 295 formed to include a spring receiving cavity 296, a second end 297 having a connector hole 298 extending therethrough, and a disk 299 extending radially from the shaft 294

between the first end 295 and second end 297. Disk 299 has a surface 201 facing first end 221 of electromagnet 265 which has a cross-sectional area substantially similar to cross-sectional area of first end 221 of electromagnet 265. First end 295 of movable element 261 is received in cylindrical axial cavity 225 of core 293. Spring 292 is  
5 received in spring-receiving cavity 296 and engages closed second end 231 of core 293 to bias disk 299 away from first end 231 of core 293. Second end 297 of shaft 294 is connected by a fastener to latch 281 which is pivotally mounted about pivot axis 202 to lock core 212. Second end 297 is connected to latch 281 at a point spaced apart from pivot axis 202 to increase mechanical advantage.

10               When current flows through coil 285 of electromagnet 265 in response to receipt of an authorized code from token 210, a magnetic field is produced which attracts surface 201 of disk 299 toward first end 231 of core 293 causing latch 281 to pivot away from blocking body 289 and to disengage step 291. Blocking body 289 is immediately urged upwardly by compressed spring 275 upon disengagement of latch  
15 281 from step 291 as shown in Fig. 14. Cessation of current flow causes shaft 294 to move in the direction of arrow 211 in Fig. 12 allowing latch 281 to pivot into engagement with sidewall 288 of blocking body 289. Upon token 210 removal upper spring 287 will urge blocking body 289 to its blocking position while allowing latch 281 to be urged into engagement with step 291 as shown in Fig. 12. Thus, current  
20 need only flow through coil 285 long enough to disengage latch 281 from step 291 momentarily so that blocking body 289 can be urged upwardly out of blocker-receiving cavity 271. Because continuous current flow through coil 285 is not required to maintain the electrical portion 222 in a state in which key plug 230 rotation with respect to core body 228 is permitted, battery 182 life can be extended.

25               Referring to Figs. 15-18, a third embodiment of an electronic lock core 312 is illustrated. Electronic lock core 312 includes a core body 328, a key plug or lock actuator 330 formed to include a keyway 337, a mechanical portion 320, and an electrical portion 322. Mechanical portion 320 includes two tumbler pin barrels 336 each containing tumbler pins 344 partially extending into keyway 337 and blocking  
30 rotation of key plug 330 relative to core body 328. Electrical portion 322 includes a coupling or token communicator 356, circuit 352, an electromagnetic actuator 354, and a mechanical linkage 357. Mechanical linkage 357 includes a mechanical energy



storage system 373 having a semi-spherical tumbler pin 345, spherical tumbler pins 377, lower spring 375, upper spring 387, a blocking body 389 having a channel 391 formed therein, and a blocker-receiving cavity 371 formed in key plug 330.

Electromagnetic actuator 354 includes an electromagnet 365, a movable element 361  
5 attached by a hinge coupling to electromagnet 365, and a spring 392 biasing the unattached portions of movable element 361 away from the electromagnet 365.

Movable element 361 includes a disk-shaped ferrous element 399 having an electromagnet-facing surface 301, an opposite surface having a flange 381 extending therefrom, and a mounting bracket 384 formed at one edge. Electromagnet  
10 365 includes a core 393 and a coil 385. Core 393 includes a closed first end 321, a cylindrical outer shell 319 extending from the first end 321, a central shaft 313 extending axially from the first end 321, and a second end 331 having a mounting ear 315 extending therefrom. The core 393 is formed to include an annular opening 327 communicating with an internal cavity 329 defined by the outer shell 319, closed end  
15 321, and central shaft 317. Mounting bracket of movable element 361 is pivotally connected to mounting ear 315 of core 393, as shown, for example, in Fig. 16 so that electromagnet-facing surface 301 is directed toward second end 331 of core 393. Coil 385 and spring 392 are received in cavity 329, as shown, for example, in Fig. 16.

Electromagnetic actuator 354 is mounted in cavity 383 of lock body  
20 328 so that flange 381 of movable element 361 is biased toward channel 391 of blocking body 389 by spring 392. When current is induced to flow through coil 385, an electromagnetic field is generated which attracts disk 399 of movable element 361 toward second end 331 of electromagnet 365 causing flange 381 to pivot out of channel 391. If a token 310 including an appropriately bitted blade 346 has been  
25 inserted into keyway 337, mechanical energy storage system 373 compresses lower spring 375 to store energy which urges blocking body 389 upwardly out of blocker body-receiving channel 371 immediately upon removal of flange 381 from channel 391.

Referring to Figs. 19-21 a fourth embodiment of a lock core 412 is  
30 illustrated. Lock core 412 includes mechanical portion 420 having two tumbler pin barrels 436 each containing tumbler pins 444 extending partially into the keyway 437 blocking the rotation of key plug or lock actuator 430 with respect to core body 428

and an electrical portion 422. Electrical portion 422 includes a coupling or token communicator 456, circuit 452, an electromagnetic actuator 454, and a mechanical linkage 457. Mechanical linkage 457 includes a mechanical energy storage system 473 having a semi-spherical tumbler 445, a semi-spherical ended tumbler 477, a lower  
5 spring 475, a pivotally-mounted latch 481 having a blocker end 482, a storage end 486, and an indentation 491, a torsion spring 487, and a latch-receiving cavity 471 in the key plug 430. Before, token 410 communicates with lock core 412, blocker end 482 of latch 481 is positioned in latch-receiving cavity 471 of key plug 430 to prevent rotation of key plug 430 relative to core body 428.

10               Electromagnetic actuator 454 includes an electromagnet 465, a movable element 461, and a spring 492. Electromagnet 465 includes a core 493 having a first end 421 formed to include a circular opening 423 therethrough communicating with a cylindrical axial cavity 425 and a ring-shaped opening 427 therethrough communicating with an annular cavity 429, a closed second end 431,  
15 and a cylindrical coil 485 received in the annular cavity 429. Movable element 461 includes a shaft 494 having a first end 495 formed to include a spring-receiving cavity 496, a pointed second end 497, and a disk 499 extending radially from the shaft 494 between the first end 495 and second end 497. First end 495 of movable element 461 is received in cylindrical axial cavity 425 of core 493. Spring 492 is received in  
20 spring-receiving cavity 496 and engages closed second end 431 of core 493 to bias disk 499 away from first end 431 of core 493. Second end 497 of shaft 494 is biased by spring 492 toward and for receipt into indentation 491 of latch 481 which is pivotally mounted to lock core 412. Coil 485 and spring 492 are received in cavity 427, as shown, for example, in Figs. 19-21.

25               When a token 410 is inserted into keyway 437, bitted blade 446 positions tumbler pins 444 of mechanical portion 420 in a position which does not inhibit rotation of the key plug 430 relative to the core body 428. Bitted blade 446 also urges semi-spherical tumbler pin 445 upwardly storing energy in spring 475 that may be later released to urge storage end 486 of pivotally-mounted latch 481  
30 upwardly and pivot blocker end 482 of latch 481 from its blocking position, in which it inhibits rotation of key plug 430 with respect to core body 428, to a second position

(shown in phantom lines) in which blocker end 482 of latch 481 is no longer received in the blocker-receiving channel 471.

Blocker end 482 of latch 481 is pivoted out of the blocker-receiving channel 471 in response to removal of tip 497 of movable element 461 from  
5 indentation 491 in latch 481 after the electromagnet 465 has been momentarily energized in response to receiving an authorized code freeing the key plug 430 to rotate with respect to the core body 428.

Referring to Figs. 22-24 a fifth embodiment of electronic lock core 512 is illustrated: Lock core 512 includes a mechanical portion 520, electrical portion  
10 522, a key plug or lock actuator 530, and a core body 528. Mechanical portion 520 includes two tumbler pin barrels 536 each containing tumbler pins 544 partially extending into keyway 537 and blocking rotation of key plug 530 relative to core body 528. Electrical portion 522 includes a circuit 552, a electromagnetic actuator 554, a coupling or token communicator 556, and a mechanical linkage 557. As an  
15 alternative configuration to previously discussed embodiment of lock core 12, circuit 552 is located within cavity 583 instead of in cavity 559 in face plate 539. Mechanical linkage 557 includes a mechanical energy storage system 573, a ball bearing 533, a cam 535, and a ball bearing-receiving sleeve 541. Mechanical energy storage device 573 includes a semi-spherical ended tumbler 545, a spherical tumbler  
20 577, a lower spring 575, an upper spring 587, and a blocker body 589 having an annular indentation 591. Cam 535 is attached to rotatable element 543 of a rotational solenoid 547. Ball bearing 533 is received in sleeve 541 which opens at one end 549 adjacent to blocker body 589 and at the other end 551 adjacent to a cam 535. Cam 535 has a first surface 553, a second surface 555, and an inclined surface 579  
25 extending between the first and second surfaces 553, 555. Cam 535 is positioned so that when ball bearing 533 engages first surface 553 of cam 535, ball bearing 533 is held securely within indentation 591 in blocking body 589.

When a token 510 is initially inserted into keyway 537, bitted blade 546 aligns tumbler pins 544 of mechanical portion 520 to not inhibit rotation of key  
30 plug 530 relative to core body 528. Bitted blade 546 also engages and urges semi-spherical tumbler 545 upwardly compressing lower spring 575 of mechanical energy storage system 573. Compressed lower spring 575 stores energy for moving blocker

body 589 upon removal of ball bearing 533 from indentation 591 of blocker body 589. However, until a valid authorization code is received and rotational solenoid 547 is energized, ball bearing 533 is securely held within indentation 591 preventing blocking body 589 from moving upwardly out of blocker-receiving cavity 571 formed in key plug 530. Therefore, electrical portion 522 continues to inhibit rotation of key plug 530 relative to core body 528.

If token 510 sends a valid access code to electronic core 512, rotational solenoid 547 rotates 180 degrees from the position shown in Figs. 22-23 to the position shown in Fig. 24. During the rotation of rotatable shaft 543 of rotatable solenoid 547, ball bearing 533 is urged out of indentation 591 by upward motion of blocking body 589 so that ball bearing 533 rides along inclined surface 579 to second surface 555 of cam 535. Blocker body 589 is urged upwardly by the energy previously stored in lower spring 575. Upward movement of blocking body 589 causes blocking body 589 to not be received in blocker-receiving cavity 571 and therefore to not block rotation of the key plug 530 relative to the core body 528. Upward movement of blocker body 589 also compresses upper spring 587 to store energy to facilitate return of blocker body 589 to its blocking state upon removal of bitted blade 546 from keyway 537.

Once blocker body 589 has moved upwardly, ball bearing 533 engages sidewall 588 of blocker body 589 and is squeezed between second surface 555 and side wall 588 mechanically preventing cam 535 and movable element 543 of rotational solenoid 547 from returning to their initial orientations. Although rotatable element 543 is spring 592 biased to return to the position shown in Figs. 22-23 when no current flows through solenoid 547, it is prevented from doing so by the above squeezing action. Thus, rotational solenoid 547 no longer needs to be energized to maintain it in the non-blocking position allowing power consumption of electrical portion 522 of lock core 512 to be reduced.

When bitted blade 546 is removed from keyway 537, upper spring 587 expands and urges blocking body 589 downwardly into blocker-receiving cavity 571. During this downward movement, ball bearing 533 follows side wall 588 of blocking body 589 until it is forced back into indentation 591 of blocking body 589. Thus no

electrical power is consumed to restore lock core 512 to a state in which key plug 530 is prohibited from rotating relative to lock core 528.

As previously mentioned, the circuits 48, 52 and contacts or couplings 50, 56 used in each of the five specifically described embodiments may vary as to their configurations and individual components. Various examples of circuit 48, 52 configurations are illustrated and described in provisional application Serial No. 60/080974 that is expressly incorporated by reference. Contacts and couplings 50, 56 including metallic contacts, conductive elastic contacts, capacitive couplings, inductive couplings, optical couplings and combinations of the aforementioned are also illustrated and described in the provisional application. Additional examples of circuits 48, 52 and contacts or couplings 50, 56 are described and illustrated in U.S. Patent No. 5,870,915, U.S. Patent No. 5,870,913, U.S. Patent No. 5,841,363, U.S. Patent No. 5,836,187, U.S. Patent No. 5,826,499, and U.S. Patent No. 5,823,027, the disclosures of which are specifically incorporated herein by reference.

As outlined above, token and lock core circuits 48, 52 include many features that can be combined in various ways. In all embodiments of token circuits 48, the token circuit 48 includes token identification information 74 that communicates with the token identification reader 58 of lock core 12 through a token operator 75. The lock operator 60 of lock core circuit 52 considers the information contained in token identification information 74 to determine whether to grant or deny access to the user of token 10.

The recombination system 62 of lock core circuit 52 communicates with lock operator 60 to program lock operator 60 as to which tokens 10 should be granted permission to rotate key plug 30, control sleeve 32, and control lug 34. In conventional mechanical lock cores, the recombination system included changing the number or size of tumbler pins in pin tumbler barrels as disclosed, for example, in U.S. Pat. Nos. 4,424,693, 4,386,510, and 4,444,034. Recombinating the mechanical portion 20 of lock core 12 is accomplished by changing the number and size of tumbler pins as described in these patents.

The electronic recombination of circuit 52 via recombination system 62 may be accomplished by 1) inserting a "recombining token" into lock core 12 and the recombining token communicating with recombination system 62 through

- contact 56 of lock core 12; 2) placing a contact (not shown) on face plate 39 of lock core 12 that can "connect" the recombination system 62 with a user through scanning, infrared, optical, and physical connection techniques; 3) removing lock core 12 using control token 42 to access a contact not positioned on face plate 39 or keyway 37; or
- 5 4) any other type of communication technique.

Any of the following components may be used to connect a user and recombination system 62 so that a user can communicate with recombination system 62: metallic contacts; conductive elastic contacts; capacitive coupling; inductive coupling; optical coupling; combination of metallic contacts and either optical,

10 inductive, or capacitive coupling; combination of conductive elastic contacts and either optical, inductive, or capacitive coupling; the above power and communications methods in combination with the Token ID Reader (i.e., through a recombination token).

The lock core circuit 52 may also include a clock 66 that cooperates

15 with lock operator 60 to recombine lock operator 60 at certain times. By recombining lock operator 60 in this manner, a first token 10 may be granted access through lock core 12 only for a selected twelve hours of a day and a second token may be granted access through the same lock core 12 only for the other twelve hours of a day. This type of recombination could grant users access only during the time

20 periods when they are to be in a facility.

The lock core circuit 52 and/or token circuit 48 may include a token access history 64, 78 that records the tokens 10 which have communicated with lock core 12. In some embodiments, the lock core circuit 52 and/or token circuit 48 also include a clock 66, 80 communicating with token access history 64, 78 to provide the

25 time when the tokens 10 communicated with lock core 12. A user may communicate with token access history 64, 78 in the same manner and using the same components as described above for recombination system 62.

Any of the following components may be used as clock 66, 80: timekeeping electronic circuit (such as those made by, Dallas Semiconductor,

30 Panasonic); timekeeping algorithm in lock operator 60.

The token access history 64, 78 may include a static random access memory. The static random access memory always requires power and thus a power

source 68, 82 must be located in the same circuit 48, 52 as token access history 64, 78 including a static random access memory. When a token 10 is not communicating with lock core 12, the static random access memory does not require much power. The static random access memory requires significantly more power when a token 10  
5 is communicating with lock core 12.

The token access history 64 may also include an Electrically Erasable Programmable Read-Only Memory ("EEPROM"). The EEPROM does not need external power from a power source 68, 82 because the EEPROM includes a capacitor that discharges over a lifetime of approximately 10 years. In alternative  
10 embodiments, the token access history may include any type of device having the ability to store information concerning tokens that communicate with a lock core, download that information, and meet the power and space restrictions imposed by the lock core and token.

Another form of recombination or downloading access history  
15 information is through token 10 receiving information from a first lock core 12 and then transmitting that information to a second lock core 12. For example, the security system of facility could include the lock cores on the outer perimeter of the facility hard-wired into a central database and lock cores 12 within the facility that operate as standalone units. As a token 10 is used to enter the outer perimeter of the facility, the  
20 central database could download recombining information onto the token circuit 48. Then, as the token 10 is used in lock cores 12 within the facility, the token circuit 48 would recombine the lock core circuits 52. While the token 10 is within lock core 12, token access history information from the lock core circuit 52 is downloaded onto the token circuit 48. Later, as the token 10 is used to exit the outer perimeter of the  
25 facility, the token history information is downloaded to the central database from token circuit 48.

As discussed above, because lock core 12 is a standalone unit, either token 10, lock core 12, or both token 10 and lock core 12 must include a power source 68, 82 that provides power to lock operator 60, actuator 54, recombination system 62,  
30 token access history 64, 78 token identification reader 58, clock 66, 80, token operator 75, and token identification information 74. If power source 82 is located in token 10, the power will be transmitted into lock core circuit 52 through token identification

reader 58. The power received from token 10 is then sent to a power conditioner 70 to place the power in a usable form and then to a power distributor 72 which distributes power to all of the power-consuming components of lock core 12. If power source 68 is located in lock core 12, the power will be transmitted into token  
5 circuit 48 through token operator 75.

Power conditioner 70 could be any of the following components: 7800 or 7900 type linear power regulator, switching regulator, charge pump, Zener regulator, battery charger and regulator combination circuit.

Power distributor 72 could be any of the following components: wires;  
10 circuit board traces, connectors, metallic contacts, conductive elastic contacts.

The power source 68, 82 could be located in both lock core 12 and token 10. This type of power source 68 configuration could, for example, include a power source 68 in lock core circuit 52 that provides continuous power to clock 66 of lock core circuit 52 and a power source 82 in token circuit 48 that provides power to  
15 the other power-consuming components of lock core 12 only when token 10 interacts with lock core 12. Compared to a configuration wherein the entire power source 68 is located within lock core circuit 52, this configuration wherein the power source 68, 82 is divided between lock core 12 and token 10 frees up more space in lock core 12 for other mechanisms.

20 The power source 68, 82 may be any type of device that provides the necessary amount of power to the components requiring power. The power source 68, 82 could be one of the following items: electrochemical battery such as those made by Duracell, re-chargeable electrochemical battery, capacitor, super capacitor such as the P695X series made by Panasonic, magneto current generator, piezoelectric  
25 polymer film or piezoelectric ceramic electric generator.

In addition, the power could be generated solely or supplemented by power generated by a user of token 10. This power could be generated by the user gripping the token 10 or rotating or sliding the token 10 in the lock core 12. For example, the lock core could include a slidable flap positioned within the keyway 37  
30 that token 10 would engage and move upon sliding token 10 into and through keyway 37. The flap could be connected to any power source 68,82 or power conditioner 70 and power distributor 72 mentioned within this application. Further, this flap could



be positioned near the front of lock core 12 to provide protection to components contained within lock core 12.

A piezoelectric material that possesses the ability to generate an electrical potential when subjected to a mechanical strain may be used to generate power from the user's movement of token 10. In addition a magneto may be used to generate power from a user operating token 10.

Various lock core circuits 1120, 1122, 1124, 1126, 1128, 1130, 1132, 1134, 1136, 1138, 1140, 1142, 1144, 1146, 1148, 1150 having different combinations of the above elements are shown in Figs. 29-44 . Lock core circuit 1120 is shown in Fig. 29 and includes token ID reader 58, lock operator 60, recombination system 62, clock 66, and power source 68. The clock 66, recombination system 62, and token ID reader 58 all feed into lock operator 60 and lock operator 60 processes all the information and determines whether to permit actuator 54 to move mechanical linkage 57 so that key plug 30 can rotate relative to core body 28. The input to lock core circuit 1120 through token identification reader 58 is token identification information 114 and the output from lock core circuit 1120 through token identification reader 58 is token access history information 116. Lock core circuit 120 could be used with a token circuit 48 having token access history 78 that would receive and store token access history information 116. In addition, lock core 1120 provides a power output 118 that can provide power to components of token circuit 48. Token identification information 114, token access history information 116, and power output 118 can flow through the same or separate contacts 50, 56.

Lock core circuit 1122 is shown in Fig. 30 and is identical to lock core circuit 1120 except that lock core circuit 1122 includes a power source 68 that only provides power to clock 66. The power for the remaining components is provided in the form of power input 118 provided from a power source 82 in a token 10. The power input 118 is input into lock core circuit 1122 through token identification reader 58 and sent through a power conditioner 70 and power distributor 72 before being transmitted to all of lock core circuit 1122 components requiring power.

Lock core circuit 1124 is shown in Fig. 31 and is identical to lock core circuit 1120 except that lock core circuit 1124 includes a token access history 64.

Token access history 64 receives and stores information from lock operator 60 including, if desired, information from clock 66.

Lock core circuit 1126 is shown in Fig. 32 and is identical to lock core circuit 1124 except that lock core circuit 1126 includes a power source 68 that only provides power to clock 66. The power for the remaining components of lock core circuit 1126 is provided in the form of power input 118 provided from a power source 82 in a token 10.

Lock core circuit 1128 is shown in Fig. 33. Lock core circuit 1128 is identical to lock core circuit 1120 except that lock core circuit 1128 does not include a clock 66. Because lock core circuit 1128 does not include either clock 66 or token access history 64, lock core circuit 1128 sends all token access history information 116 to token 10 to be stored by token circuit 48 if token circuit 48 includes token access history 78.

Lock core circuit 1130 is shown in Fig. 34 and is identical to lock core circuit 1128 except that lock core circuit 1130 does not include a power source 68 and thus receives all required power from a power input 118. Power received through power input 118 is generated by a power source 82 located in token circuit 48.

Lock core 1132 is shown in Fig. 35 and is identical to lock core circuit 1128 except that lock core circuit 1132 includes a token access history 64.

Lock core circuit 1134 shown in Fig. 36 is identical to lock core circuit 1132 except that lock core circuit 1134 does not include a power source 68 and thus receives all required power from power input 118.

Lock core circuits 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150 shown in Figs. 37-44 do not include a recombination system 62 and thus lock operator 60 of these lock core circuits 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150 cannot be changed. These lock core circuits 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150 are used with tokens 10 having token circuits 48 that include information about which lock cores 12 the tokens 10 are granted access to use. Thus, the token circuits 48 are "recombined" instead of the lock core circuits 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150. The differences between lock core circuits 1136, 1318, 1140, 1142, 1144, 1146, 1148, and 1150 are similar to the differences between lock core circuits 1120, 1122, 1124, 1126, 1128, 1130, 1132, and 1134

shown in Figs. 29-36. Those differences are basically whether the lock core circuit includes a token access history 64, clock 66, power source 68, or power conditioner and distributor 70, 72.

Various token circuits 1152, 1154, 1156, 1158, 1160, 1162 having  
5 various combinations of token access history 78, clock 80, and power source 82 are shown in Figs. 45-50. Token circuit 1152 is the simplest token circuit and includes only token identification information 74 and token operator 75 as shown in Fig. 45. All power required to operate token circuit 1152 is received from a power source 68 in a lock core circuit 52 through power input 118. The only output of token operator  
10 75 is token identification information 114 that is used by lock operator 60 of lock core circuits 52.

Token circuit 1154 is identical to token circuit 1152 except that token circuit 1154 includes a power source 82 as shown in Fig. 46. Thus, instead of receiving power, token circuit 1154 outputs power 118 to be used by a lock core  
15 circuit 52.

Token circuit 1156 is shown in Fig. 47 and is identical to token circuit 1152 except that token circuit 1156 includes token access history 78. Token circuit 1156 receives token access history information 116 from lock core circuits 52 and stores that information in token access history 78.

20 Token circuit 1158 is identical to token circuit 1156 except that token circuit 1158 includes a power source 82 as shown in Fig. 48. Token circuit 1160 is identical to token circuit 1152 except that token circuit 1158 includes a clock 80 and a power source 82 as shown in Fig. 49. The power source 82 could be used solely to power clock 80, all components of token circuit 1160, or all components of token  
25 circuit 1160 and a lock core circuit 52 through power input 118. The clock 80 could be used to provide time information to a token access history 64 of a lock core circuit 52 or to provide time information to a lock operator 60 of a lock core circuit 52 to assist lock operator 60 in determining if a token 10 should be granted access.

Token circuit 1162 is identical to token circuit 1160 except that token  
30 circuit 1162 includes token access history 78 as shown in Fig. 50. All of the tokens circuits 1152, 1154, 1156, 1158, 1160, 1162 can be used with lock core circuits 1120, 1122, 1124, 1126, 1128, 1130, 1132, 1134, 1136, 1138, 1140, 1142, 1144, 1146,

1148, 1150 except that one of the circuits must include a power source 68, 82 providing power to all power-consuming components. While some combinations of the circuits may provide redundant functions such as clock 66, 80 and token access history 64, 78, these redundant functions can be used to verify operations.

5                   Another preferred embodiment of a lock core 1212 and token 1210 is shown in Figs. 51 and 52. Lock core 1212 does not include a mechanical portion and thus token 1210 does not need to include a mechanical portion except to the extent that token 1210 must be able to rotate key plug 30. Instead, lock core 1212 includes an electrical portion 1214 having an electrical circuit 1216, first and second actuators  
10   1218, 1220, and first and second mechanical linkages 1222, 1224. Actuators 1218, 1220 may be the same type of actuators as described above for actuator 54. In addition, mechanical linkages 1222, 1224 may be the same type of linkages described above for linkage 57. Each of actuators 1218, 1220 interact with mechanical linkages 1222, 1224 in the same manner as actuator 54 and mechanical linkage 57.

15                   Token 1210 includes an electrical portion 1226 that interacts with electrical portion 1214 of lock core 1212 to permit rotation of key plug 30 alone or key plug 30, control sleeve 32, and control lug 34 together. Because lock core 1212 does not include a mechanical portion, electrical portion 1214 of lock core 1212 must determine if token 1210 presented to lock core 1212 should be granted access and  
20   determine if the token 1210 presented is a control token 1228 or an operating token 1230.

                  Before token 1210 is presented to lock core 1212, first mechanical linkage 1222 couples key plug 30 to core body 28 and second mechanical linkage 224 couples key plug 30 and control sleeve 32 to core body 28. When token 1210 is  
25   inserted into keyway 37 of lock core 1212, token 1210 engages first mechanical linkage 1222 to transfer energy from the movement of token 1210 to mechanical linkage 1222 in the same manner that token 10 transferred energy to mechanical linkage 57 as discussed above. While token 1210 engages first mechanical linkage 1222, token 210 does not engage second mechanical linkage 1224. In alternative  
30   embodiments, second mechanical linkage could also engage the token or first mechanical linkage could be similar to second mechanical linkage and not engage the token.

First mechanical linkage 1222 is the same as mechanical linkage 57 and includes first and second portions 1232, 1234 that have abutting faces positioned relative to an interface 1236 between key plug 30 and core body 28 as shown in Fig. 51. Second mechanical linkage 1224 includes three portions 1238, 1240, 1242 having  
5 abutting faces positioned relative to an interface 1244 between key plug 30 and control sleeve 32 and an interface 1246 between control sleeve 32 and core body 28. Before electrical circuit 1216 causes first actuator 1218 to move first linkage 1222, the portions 1232, 1234 of linkage 1222 are positioned so that core body 28 and key plug 30 are coupled together. Before electrical circuit 1216 causes second actuator  
10 1220 to move second linkage 1224, the portions 1238, 1240, 1242 of mechanical linkage 1224 are positioned so that portions 1238, 1240, 1242 couple control sleeve 32 and key plug 30 to core body 28.

When a proper operating token 1230 is presented to lock core 1212, electrical portion 1214 of lock core 1212 causes both actuators 1218, 1220 to operate  
15 to move first and second linkages 1222, 1224 to a position so that control sleeve 32 and control lug 34 are coupled to core body 28 through second linkage 1224 and key plug 30 is permitted to rotate relative to core body 28 and control sleeve 32 as shown in Fig. 51. More specifically, first actuator 1218 moves first linkage 1222 in a position so that neither of portions 1232, 1234 couple key plug 30 to core body 28.  
20 Second linkage 1224 is moved to 1) position portion 1238 of second linkage 1224 in a manner to couple control sleeve 32 and core body 28 and 2) position the abutting faces of portions 1240 and 1242 at interface 1244 between key plug 30 and control sleeve 32 so that key plug 30 is rotatable relative to core body 28 and control sleeve 32. This positioning of first and second linkages 1222, 1224 permits key plug 30 to  
25 rotate relative to core body 28 and control sleeve 32.

When a proper control token 1228 is presented to lock core 1212, electrical portion 1214 of lock core 1212 causes both actuators 1218, 1220 to move mechanical linkages 1222, 1224 to a position to permit key plug 30 and control lug 34 to rotate together as shown in Fig. 52. First linkage 1222 is moved to the same  
30 position as when proper operating token 1230 is inserted permitting key plug 30 to rotate relative to core body 28. Second actuator 1220 moves second linkage 1224 to position portions 1238, 1240, 1242 so that 1) abutting faces between portions 1238

and 1240 are at interface 1246 between control sleeve 32 and core body 28 and control sleeve 32 is rotatable relative to core body 28 and 2) portion 1242 couples control sleeve 32 and key plug 30 together. This positioning of second linkage 1224 permits key plug 30 and control sleeve 32 to be rotated relative to core body 28.

5                   The description of portions 1232, 1234 of first mechanical linkage 1222 and portions 1238, 1240, 1242 of second mechanical linkage 1224 are for illustrative purposes only to illustrate how linkages 1222, 1224 are moved to couple and uncouple key plug 30, control sleeve 32, and core body 28.

                  Various electrical lock core circuits 1250, 1252, 1254, 1256, 1258, 10   1260, 1262, 1264, 1266, 1268, 1270, 1272, 1274, 1276, 1278, and 1280 that can be used in lock core 1212 are shown in Figs. 53-68. Lock core circuits 1250, 1252, 1254, 1256, 1258, 1260, 1262, 1264, 1266, 1268, 1270, 1272, 1274, 1276, 1278, and 1280 are identical to lock core circuits lock core circuits 1120, 1122, 1124, 1126, 1128, 1130, 1132, 1134, 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150, 15   respectively, of lock core 12 except that lock operator 60 communicates with two separate actuators 1218, 1220 in lock core circuits 1250, 1252, 1254, 1256, 1258, 1260, 1262, 1264, 1266, 1268, 1270, 1272, 1274, 1276, 1278, and 1280 and a single actuator 54 in lock core circuits 1120, 1122, 1124, 1126, 1128, 1130, 1132, 1134, 1136, 1138, 1140, 1142, 1144, 1146, 1148, and 1150. The electrical token lock core 20   circuits 1152, 1154, 1156, 1158, 1160, and 1162 that can be used in token 1210 are shown in Figs. 45-50.

                  Another preferred embodiment of a lock core 1312 is shown in Fig. 69. Lock core 1312 is identical to lock core 12 except that actuator 54 communicates with a clutch 1314 positioned to lie between lock core 1312 and throw member 18 instead 25   of mechanical linkage 57. All other components of lock core 1312 are identical to lock core 12 and are numbered similarly.

                  The mechanical linkage 57 of lock core 12 and mechanical linkages 1222, 1224 of lock core 1212 can be referred to as brakes. The clutch 1314 and brakes 57, 1222, 1224 operate to permit key plug 30 to rotate alone or together with 30   control sleeve 32 and control lug 34 if a proper token 10 is presented to lock core 12, 1312. However, clutch 1314 and brakes 57, 1222, 1224 permit the rotation in different manners. As discussed above in reference to actuator 54, brakes 57, 1222,

1224 do not permit key plug 30 or control lug 34 to rotate until circuit 52, 1216 permits actuator 54 to operate to move brakes 57, 1222, 1224. Clutch 1314 always permits token 10 to rotate key plug 30, but key plug 30 does not rotate throw member 18 until electrical circuit 52 permits clutch 1314 to operate. Using brakes 57, 1222, 5 1224 may permit a vandal to "overtorque" brakes 57, 1222, 1224 by shearing the mechanism coupling key plug 30 and core body 28. Once the mechanism is sheared, the vandal may be able to rotate the key plug 30, throw member 18, and control lug 34 and achieve unauthorized access. To prevent a vandal from achieving unauthorized access, the token could be designed to break before the actuator brake 10 57, 1222, 1224 is overtorqued.

Another preferred embodiment of a lock core 1322 is shown in Fig. 70. Lock cores 12, 1212, 1312, and 1322 include a front side 92 and a back side 94. Lock core 1322 is identical to lock core 12 except that mechanical portion 20 of lock core 1322 is positioned to lie near front side 92 of lock core 1322 and electrical portion 22 15 of lock core 1322 is positioned to lie near back side 94 of lock core 1322. Basically, lock core 1322 and lock core 12 are identical except that the positions of mechanical and electrical portions 20, 22 within the lock cores are reversed. Because mechanical portion 20 moved near front side 92 of lock core 1322, control sleeve 32 is positioned to lie near the front side 92 of lock core 1322 as opposed to near the back side 94 of 20 lock core 12. Thus, lock core 1322 will include a control lug (not shown) coupled to control sleeve 32 that is positioned near the front side 92 of lock core 1322 compared to control lug 34 of lock core 12 that is positioned to lie near the back side 94 of lock core 12.

Because the position of the control lug of lock core 1322 is near front 25 side 92 of lock core 1322, lock core 1322 is not interchangeable with conventional lock cores. As discussed above, lock cylinders 14 that receive the conventional lock cores include a recess 38 that receives control lug 34. This recess 38 is positioned to receive a control lug 34 that is located near back side 94 of a lock core such as in lock core 12 as shown in Fig. 1. Thus, if lock core 1322 is used, the lock cylinder that 30 receives lock core 1322 must include a recess positioned to receive a control lug located near front side 92 of the lock core 1322.

In alternative embodiments, the lock core does not need to include a control lug or be interchangeable. For example, Schlage® produces a Primus™ lock core and Corbin-Ruswin® produces a 2000 Series™ lock core that are not interchangeable. The present invention can be incorporated into such  
5 noninterchangeable lock cores.

Tokens 10, 1210 can include many different types of electrical contacts  
50 that communicate with electrical contacts 56 in lock cores 12, 1212, 1312, 1322. Several types of contacts and token are shown in Figs. 71-76. A token 1330 having an electrical circuit 1332 and electrical contact 1334 is shown in Fig. 71. Token 1330  
10 further includes a bow 1336 and a bitted blade 1338 having a proximal end 1340 coupled to bow 1336 and a distal end 1342 spaced apart from proximal end 1340. Electrical circuit 1332 is positioned to lie in bow 1336 and electrical contact 1334 is positioned to lie at distal end 1342 of bitted blade 1338.

Another embodiment of a token 1350 and electrical contact 1352 is  
15 shown in Fig. 72. All components of token 1350 except contact 1352 are identical to token 1330 and numbered similarly. Electrical contact 1352 is positioned to lie between the proximal and distal ends 1340, 1342 of bitted blade 1338 and extend through a side of bitted blade 1338.

A token 1360 having an electrical circuit 1370 and inductance type  
20 electrical contact 3162 is shown in Fig. 73. Token 1360 includes a bow 1364 and blade 1366 coupled to bow 1364. Inductance type electrical contact 1362 includes a coil 1368 that is positioned to lie within blade 1366 of token 1360. Token 1360 having inductance type electrical contact 1362 is used with a lock core 12, 1212, 1312, 1322 having an electrical contact 56 configured to communicate with such an  
25 inductance type electrical contact 1362.

In the tokens 1330, 1350, 1360 shown in Figs. 71, 72, and 73, the electrical circuits 1332, 1370 are all positioned to lie in bow 1336, 1364 and electrical contacts 1334, 1352, 1362 are positioned to lie in blade 1338, 1366. In alternative  
30 embodiments, each of the electrical circuits and electrical contacts could be positioned to lie in either the blade, bow, or both. For example, both the electrical circuit and electrical contact could be positioned to lie in the bow as shown, for example, in U.S. Patent No. 5,003,801 to Stinar which is incorporated herein by reference.



A token 1380 having a bow 1382, a bitted blade 1384 coupled to bow 1382, and a cylindrical blade 1386 appended to bow 1382 is shown in Fig. 53. Bitted blade 1384 can include an electrical contact (not shown) and be used in lock cores that include only a mechanical portion, only an electrical portion, or both mechanical and electrical portions. Cylindrical blade 1386 could be used in different types of lock cores that include only electrical portions. Cylindrical blade 1386 includes electrical contacts 1388 in the form of a plurality of strips 1390 on the outer surface of cylindrical blade 1386. The lock core that cylindrical blade 1386 communicates with may only include a single electrical contact strip and thus the plurality of strips 1390 on cylindrical blade 1386 permit cylindrical blade 1386 to be placed in the lock core in several different orientations and still communicate with the lock core.

In the illustrated embodiment of Fig. 74, cylindrical blade 1386 extends substantially perpendicular relative to bitted blade 1384. In alternative embodiments, the cylindrical blade and bitted blade may be oriented at different angles relative to each other as long as both the cylindrical blade and bitted blade can be inserted into a lock core.

Another preferred token 1410 is shown in Fig. 75. Token 1410 includes a bow 1412 and a triangular-shaped blade 1414 coupled to bow 1412. The token 1410 further includes electrical contacts 1416 in the form of elongated strips 1418 extending along two of the three sides of the triangular-shaped blade 1414.

Another preferred embodiment of a token 1420 is shown in Fig. 76. The token 1420 includes a bow 1422, a bitted blade 1424 coupled to the bow 1422, and an electrical contact 1426 positioned on bitted blade 1424. A portion of a lock core electrical contact 1428 that communicates with token electrical contact 1426 is also shown in Fig. 76.

The electrical contact 56 in lock core 12, 1212, 1312, 1322 that communicates with electrical contacts 1334, 1352, 1362, 1388, 1416, 1426 must be located within lock core 12, 1212, 1312, 1322 so that the electrical contacts 56, 1334, 1352, 1362, 1388, 1416, 1426 can communicate. The electrical contacts 56, 1334 can communicate through direct physical interaction, infrared, and optical techniques. More specifically, any of the following components can be used as electrical contacts 56, 1334, 1352, 1362, 1388, 1416, 1426: metallic contacts; conductive elastic

contacts; capacitive coupling; inductive coupling; optical coupling; combination of metallic contacts and either optical, inductive, or capacitive coupling; combination of conductive elastic contacts and either optical, inductive, or capacitive coupling.

Another embodiment of a token is a rechargeable token. To save space  
5 in the token and lock core, the power source could be a rechargeable battery positioned to lie in the token. The rechargeable token could be recharged by placing the token in a charger when the token is not needed (i.e., when the user is sleeping at night). The token could also be recharged by being carried in a token holder that continuously charges the token. The token could fold out, slide out, snap out, etc. of  
10 the token holder.

The tokens and electrical contacts shown in Figs. 71-76 are only exemplary of the types of tokens and electrical contacts that can be used. In general, the token includes a blade member having a cross-sectional shape that is accepted in an opening formed in a lock core. The token also includes electrical contacts that  
15 engage contacts included in the lock core. In addition, the cross-sectional shape of the blade member permits the member to rotate a portion of the lock core. In alternative embodiments, other types of tokens and electrical contacts may be used.

As discussed above, one or both of the token and lock core must include a power source 68, 82. Figs. 77, 78, and 79 shown possible locations of a  
20 power source 68, 82 (in phantom) including the blade or bow of token 10 and lock core 12, respectively.

The present invention also includes locking systems having tokens that are empowered to perform selected functions. A conventional locking system typically includes a lock core mounted to a door, wall, box, cabinet, etc. and a token  
25 that cooperates with the lock core to permit a user access through the door or into the box, cabinet, etc. Conventional tokens include bitted keys that are "cut" to fit into selected lock cores. Once a bitted key is made, it may not readily or easily be reconfigured to fit into a different lock core.

A token 1450 is provided that can be programmed or charged to  
30 perform selected functions. Before being charged, the token 1450 is not able to perform any functions. The token 1450 may be programmed, for example, to be inserted into only selected lock cores and/or inserted into selected lock cores in a

certain order. These programmable tokens 1450 may also be “read” after use to determine the lock cores in which the token 1450 was inserted and the time when the token 1450 was inserted in the lock core.

5 A programmable token 1450, token information programmer 1452, and token power charger 1454 are shown in Figs. 80, 81, and 82. The programmable token 1450 is stored in token power charger 1454 until the token 1450 is needed as shown in Fig. 80. When the token 1450 is needed to perform a particular function, the token 1450 is placed in token information programmer 1452 to receive information about the functions it is to perform.

10 The token 1450 includes a bitted blade 1456, a handle 1458, and an electrical portion (not shown) that receives and stores the information received from token information charger 1452 and later uses that information to communicate with lock cores. The electrical portion may be any of the token electrical portions discussed above. In alternative embodiments, a bitted blade is not required and the  
15 token may operate a lock core or other locking mechanism through electrical communication alone.

The token 1450 also includes a killswitch 1460 having a lever 1462 coupled to handle 1458 and an electrical contact 1464 coupled to handle 1458 that lever 1462 can engage and disengage as shown in Figs. 81 and 82. The token 1450  
20 can be programmed so that a user must depress lever 1462 to engage contact 1464 once token 1450 is charged for token 1450 to be able to perform its selected functions. If the user releases lever 1462 so that lever 1462 disengages contact 1464, then token 1450 is not able to operate to perform any additional functions. This is useful in a prison or other high security application where the user of the charged token 1450 can  
25 release lever 1462 and deactivate token 1450 if the user is overcome by anyone seeking access to token 1450. In alternative embodiments, the killswitch may include different components. In alternative embodiments, a killswitch is not required.

Although the invention has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope  
30 and spirit of the invention as described and defined in the following claims.